

UNICOMP : UNX330

เครื่องตรวจจับโลหะแบบเดินผ่าน

(33 Zones Walk Through Metal Detector)



Model : UNX330

The high-performance walk through metal detector has the following advantages: high metal detection sensitivity; high anti-interference ability; multiple detection area and each region can be set sensitivity individually; self-diagnosis program, power-on self-test; 7-inch large LCD touch Screen; high-strength materials, anti-corrosion etc . ; monitor the background environment in real time.

Features

1. Multi-zone technology: 33 detection zones, adjust sensitivity of each zone individually.
2. Touch screen: 7-inch HDMI LCD touch screen, easy to operate and understand.
3. Mobile connection technology: realize mobile APP remote control (optional).
4. IP Grade: IP54 superior waterproof performance (optional)
5. Self calibration once power on.
6. Self diagnostic, it will inform the user when exit the system.
7. Start-stop technology: infrared devices with automatic start-stop technology.
8. Adjust the alarm sounds arbitrarily.
9. Adjust the working frequency automatically or manually.
10. Detection Technology: Even detection technology, no blind spot.
11. Professional detection process: built in 72 different detection occasions (providing upgrade services).
12. Security level: 100 security levels.
13. Detection sensitivity of each zone: From 0 to 255 level.
14. Multi-alarm sounds to choose-to fit different applications.
15. Statistics: Record the pass and alarm numbers
16. Query function: The system has real-time information query function.
17. Intelligent Standby: The system has intelligent standby operation alerts.
18. Working Standby: 16 high-brightness LED indicator on.
19. Detection speed: more than 60-150 people pass and detect in 1 minute.

Specification

○ Model	33 Zones 7 inch Screen Walk Through Metal Detector UNX330
○ Vertical Dimension	2240×670×850mm
○ Vertical Tunnel Size	2000×700mm
○ Package Size	2280×700×290mm
○ NW	67KG
○ GW	75KG
○ Working Voltage	AC90V ~ 240V 50 / 60Hz
○ Power Consumption	20W
○ Working Frequency	1—100 个频段
○ Working environment	-20°C ~ 65°C
○ Installation Environment	100cm* (L) 200cm (no metal in this range)
○ Highest standard	Metal size ≥ 6g

Note: "●" means own this configuration, "○" means could be optional, "/" means no such configuration.

Technical Parameters:

○ Electrical appliances with reference to EN60950 safety standards	conform
○ Radiation is carried out with reference to EN50081-1	conform
○ Anti-interference with EN50082-1 standard implementation	conform
○ Implementation (GB15210-2003) version of the walk through metal detector standard	●
○ Enterprises through ISO9001: 2008 quality management system certification	●
○ Enterprises through OHSAS1 8001 occupational health certification	●
○ Enterprises through the ISO14001 environmental management certification	●
○ Products through the EU CE certification	●
○ FCC	●
○ ROHS	●

Note: "●" means own this configuration, "○" means could be optional, "/" means no such configuration.

Technical Standard:

○ The portable metal can be removed	●
○ Double high brightness red and green digital display	/
○ 7 inch LCD touch screen	●
○ Simple and intuitive touch operation panel	●
○ One-button mobile phone remote control mode of operation	○
○ Multiple networking interfaces	○
○ External control alarm device port	●
○ Secondary development port / upgrade port	●
○ Statistical functions	●
○ Alarm count statistics function	●
○ Data query function	●
○ System double password protection function	●
○ Multi-location simultaneous detection of simultaneous alarm function	●
○ Large item detection intelligent division function	●
○ Super brightness intelligent partition alarm indicator	●
○ Super brightness double row position indicator	●
○ 6 select frequency degree	/
○ 100 selected the working frequency	●
○ Alarm sound mute mode setting	●
○ Alarm sound size adjustable mode	●
○ Multiple alarm sound selection mode	●
○ Front and rear unilateral location alarm indicator	○
○ Front unilateral location alarm indicator	/
○ Front double location alarm indicator	●
○ Front and rear four position alarm indicator / optional	○
○ The sensitivity of each detection zone is adjustable	●
○ The sensitivity of each detection zone is adjustable0-255	●
○ The sensitivity of each detection zone is adjustable0-120	/
○ Security class can be selected 1-6	/
○ Security class can be selected 1-100	●
○ Interactive 33 zones	●
○ Built-in 72 different occasions to detect standard procedures	●
○ Battery life is 2 hours / optional	○
○ Battery life is 8 hours / optional	○
○ Restore factory settings	●

Note: "●" means own this configuration, "○" means could be optional, "/" means no such configuration.

7-inch HDMI LCD touch screen:



High-strength plastic beams (length can be customized) :



Connector:



2280x700x290mm Package size:



More customized functions: (Optional)



Body Temperature Measure



Video Intercom System



Face Recognition System



Walk Through Detecting Video

WAC RESEARCH CO.,LTD. เลขที่ 9 ซ.ลาดพร้าววังหิน 33 ถ.ลาดพร้าววังหิน แขวงลาดพร้าว เขตลาดพร้าว กทม.10230
โทร. 025303809-10, 025381038 แฟกซ์. 025383098
E-mail: sales@wacinfotech.com เว็บไซต์ www.wacinfotech.com