

SINGULAR

SCR28I-SM33 Hybrid Smart Card Reader

Standard Features for SCR28I-SM33 Reader Series :

- Hybrid 3 in 1 magnetic card / memory card / Smart card
- RS-232 Interface
- Manual insertion
- Communication Speed 115,200 bps
- Magnetic Card Standard ISO 7811/7812/7813 (Read Only) Compliant
- Built in Magnetic Card Reader - single Head 3 track Push and Pull reading type
- Smart Card Standard ISO 7816-1/2/3, EMV and PC/SC Compliant
- Read & write microprocessor cards protocol T=0 /T=1
- Read & write EMV Card ได้
- Read & write Smart Card in ISO 7816-1,2,3 standard and EMV
- Read & write Smart Card ACOS1
- Read & write memory card เช่น SLE4406, SLE4404, SLE4418, SLE4428, SLE4432, SLE4442, EUROCHIP I, EUROCHIP II, SLE4436
- Interface library for software developer
 - 32-bits DLL files/OCX for Windows 95, 98, Me, NT 4.0 (SP5), 2000 and XP
 - C-Library for Win CE 4.x and Linux
 - PC/SC compliant IFD handler pc/sc Standard V1.0
- Compatible with most of OS : Windows 95,98, Me,NT and 2000, Linux, XP, CE 4.x
- Driver PC/SC
- Smart Card Connector type Landing Contact type, long live operation, decrease scratch when card is contacted and protect short circuit of card contact while the card is plugged.
- Operation temperature -10~50 C
- Slim Line bezel in front and Shield with metal frame
- 5V SUPPLY, Power Consumption 10mA at SAFEMODE
- display with red LED and green LED

