

Plustek SmartPhoto F50

Share Your memories with Family and Friends

Plustek SmartPhoto F50 is a compact and handy 35mm film scanner with 1800dpi optical resolution which curtails the entire expense of developing the films to digital photographs for personal usage. It scans the films directly and brings those hidden memories back to life.

With the Two one-touch button make it absolutely easy to scan the films, just insert the film, press the button and the software converts them into digital images for updating in your photo album wherein you can easily share them with friends and love ones.

Moreover, Plustek SmartPhoto F50 is offered at very reasonable price, an ideal solution for the home users who need to upload lots of photographs onto their blogs such as Facebook, Picasa, Orkut, MSN, Flickr, etc

Plustek SmartPhoto F50



Share Your memories with Family and Friends

Product Features:

- · Two One-Touch Action Button for film scanning
- · Easy to use software for digitizing films to your photo album
- · Compact size 1800dpi film scanner
- 8 seconds fast scan
- USB bus powered





Display your memories in the digital photo frames



Upload Photos to Facebook, Fickr and MSN



Digitize film

System Requirements

IBM Compatible PC, w/ Pentium III or above / CD-ROM Drive One available USB2.0 Port / 512 MB RAM 500 MB free HDD space / High Color graphic card (VGA or higher) Microsoft Windows 2000 / XP / Vista / 7 Compatible













Headquarters: sales@plustek.com

Specification

Accessories Film Holder for Mounted slides, up to 4 slides		
Software Interpolation Dynamic Range 2.0 Color Depth 24 bit/pixel Preview Speed Approx 8 sec (600dpi) Scan Speed Approx 8 sec (600dpi) Action Button Transparency & Negative Scan Scan Method Single Pass Protocols TWAIN Compliant Environment Requirement WEEE / ROHS Interface USB 2.0 ONLY Net Weight 308.5 g Dimensions (D x W x H) Operating System Windows 2000 / XP / Vista / 7 Compatible Accessories Film Holder for Mounted slides, up to 4 slic Film Holder for Filmstrip, hold up to 6 fram	Scanning Type	Image Capture CMOS
Dynamic Range Color Depth 24 bit/pixel Preview Speed Approx 8 sec (600dpi) Scan Speed Approx 8 sec (600dpi) Action Button Transparency & Negative Scan Scan Method Single Pass Protocols TWAIN Compliant Environment Requirement WEEE / ROHS Interface USB 2.0 ONLY Net Weight 308.5 g Dimensions (D x W x H) Operating System Windows 2000 / XP / Vista / 7 Compatible Accessories Film Holder for Mounted slides, up to 4 slic Film Holder for Filmstrip, hold up to 6 fram	Optical Resolution	1800 dpi
Color Depth 24 bit/pixel Preview Speed Approx 8 sec (600dpi) Scan Speed Approx 8 sec (600dpi) Action Button Transparency & Negative Scan Scan Method Single Pass Protocols TWAIN Compliant Environment Requirement WEEE / ROHS Interface USB 2.0 ONLY Net Weight 308.5 g Dimensions (D x W x H) 104 x 155 x 100mm (4.05"x6.1"x3.93") Operating System Windows 2000 / XP / Vista / 7 Compatible Accessories Film Holder for Mounted slides, up to 4 slic Film Holder for Filmstrip, hold up to 6 fram	Software Interpolation	3600 dpi x 3600 dpi
Preview Speed Approx 8 sec (600dpi) Scan Speed Approx 8 sec (600dpi) Action Button Transparency & Negative Scan Scan Method Single Pass Protocols TWAIN Compliant Environment Requirement WEEE / ROHS Interface USB 2.0 ONLY Net Weight 308.5 g Dimensions (D x W x H) 104 x 155 x 100mm (4.05"x6.1"x3.93") Operating System Windows 2000 / XP / Vista / 7 Compatible Accessories Film Holder for Mounted slides, up to 4 slic Film Holder for Filmstrip, hold up to 6 fram	Dynamic Range	2.0
Scan Speed Approx 8 sec (600dpi) Action Button Transparency & Negative Scan Scan Method Single Pass Protocols TWAIN Compliant Environment Requirement WEEE / ROHS Interface USB 2.0 ONLY Net Weight 308.5 g Dimensions (D x W x H) 104 x 155 x 100mm (4.05"x6.1"x3.93") Operating System Windows 2000 / XP / Vista / 7 Compatible Accessories Film Holder for Mounted slides, up to 4 slic Film Holder for Filmstrip, hold up to 6 fram	Color Depth	24 bit/pixel
Action Button Transparency & Negative Scan Scan Method Single Pass Protocols TWAIN Compliant Environment Requirement USB 2.0 ONLY Net Weight 308.5 g Dimensions (D x W x H) Operating System Windows 2000 / XP / Vista / 7 Compatible Accessories Film Holder for Mounted slides, up to 4 slic Film Holder for Filmstrip, hold up to 6 fram	Preview Speed	Approx 8 sec (600dpi)
Scan Method Protocols TWAIN Compliant Environment Requirement WEEE / ROHS Interface USB 2.0 ONLY Net Weight 308.5 g Dimensions (D x W x H) Operating System Windows 2000 / XP / Vista / 7 Compatible Accessories Film Holder for Mounted slides, up to 4 slic Film Holder for Filmstrip, hold up to 6 fram	Scan Speed	Approx 8 sec (600dpi)
Protocols TWAIN Compliant Environment Requirement WEEE / ROHS Interface USB 2.0 ONLY Net Weight 308.5 g Dimensions (D x W x H) 104 x 155 x 100mm (4.05"x6.1"x3.93") Operating System Windows 2000 / XP / Vista / 7 Compatible Accessories Film Holder for Mounted slides, up to 4 slic Film Holder for Filmstrip, hold up to 6 fram	Action Button	Transparency & Negative Scan
Environment Requirement Interface USB 2.0 ONLY Net Weight Dimensions (D x W x H) Operating System Accessories Windows 2000 / XP / Vista / 7 Compatible Film Holder for Mounted slides, up to 4 slic Film Holder for Filmstrip, hold up to 6 fram	Scan Method	Single Pass
Interface USB 2.0 ONLY Net Weight 308.5 g Dimensions (D x W x H) 104 x 155 x 100mm (4.05"x6.1"x3.93") Operating System Windows 2000 / XP / Vista / 7 Compatible Accessories Film Holder for Mounted slides, up to 4 slic Film Holder for Filmstrip, hold up to 6 fram	Protocols	TWAIN Compliant
Net Weight 308.5 g Dimensions (D x W x H) 104 x 155 x 100mm (4.05"x6.1"x3.93") Operating System Windows 2000 / XP / Vista / 7 Compatible Accessories Film Holder for Mounted slides, up to 4 slic Film Holder for Filmstrip, hold up to 6 fram	Environment Requirement	WEEE / ROHS
Dimensions (D x W x H) Operating System Windows 2000 / XP / Vista / 7 Compatible Accessories Film Holder for Mounted slides, up to 4 slic Film Holder for Filmstrip, hold up to 6 fram	Interface	USB 2.0 ONLY
Operating System Windows 2000 / XP / Vista / 7 Compatible Accessories Film Holder for Mounted slides, up to 4 slic Film Holder for Filmstrip, hold up to 6 fram	Net Weight	308.5 g
Accessories Film Holder for Mounted slides, up to 4 slic Film Holder for Filmstrip, hold up to 6 fram	Dimensions (D x W x H)	104 x 155 x 100mm (4.05"x6.1"x3.93")
Film Holder for Filmstrip, hold up to 6 fram	Operating System	Windows 2000 / XP / Vista / 7 Compatible
Setup/Application CD-ROM	Accessories	

 $\ensuremath{\texttt{@}}$ 2009 by Plustek Inc. All rights reserved. All registered trademarks are the property of their respective owners.