

FS26EU

USB2.0 Dual Card Combo Reader

The Futronic FS26EU Fingerprint Reader combines Futronic's FS26E USB2.0 Fingerprint Scanner and a ISO7816 contact & ISO14443A/B contactless combo smart card reader into one device. A SAM (Secure Access Module) is also built-in to increase the device security. FS26E meets the US Federal Information Processing Standard 201(FIPS 201) for Personal Identification Verification (PIV) of Federal Employees and Contractors.

FS26EU has a powerful BlackFin DSP processor for on device image processing. It communicates with the smart card reader by internal serial interface. After a fingerprint is captured, DSP will process the image and generate a template for smart card storage, MoD (Match On Device) or MoC (Match On Card) processing.

FS26EU is an ideal device for highly secure two-factor authentication application. A user can register fingerprint and store on smart card (carried by user) and do MoD or MoC with a freshly captured fingerprint from fingerprint scanner at the time of authentication. The registered fingerprint template will never leave the smart card that further enhances the system security.

Specification-general

- USB 2.0 compatible interface, plug and play device
- With a 2 meter standard USB cable
- Small size, 120x72x42 mm
- Light weight, 250 gram
- Operation temperature: -10 to +55 Degree Celsius

Specification-Fingerprint matcher

- Fingerprint scanning window size is 16.26x24.38mm
- Image resolution is 320x480 pixel, 500 DPI
- Raw fingerprint image file size is 150K bytes
- With Live Finger Detection (LFD) feature
- Unique serial number programmed to USB Device Descriptor
- With internal memory for 100 fingerprint template storage

Typical Application

- e-Government
- e-Banking and e-Payment
- e-Healthcare
- Transportation
- Network Security



General spec

Specification-Smart card reader (ACS Contact & Contactless Reader Module)

- Contact card
 - Full speed USB interface to PC with simple command structure
 - Support ISO7816 Class A, B & C, 5V, 3V, 1.8V contact cards *
 - Support microprocessor cards with T=0 or T=1 protocol
 - Support PPS, PC/SC & CT-API (Through wrapper on top of PC/SC)
- Contactless card
 - Support ISO14443 A/B, Mifare classic cards *
 - Read/Write Speed up to 848Kbps
 - Card reading distance 30mm
 - Support PC/SC & CT-API (Through wrapper on top of PC/SC)
- SAM
 - Support ISO7816 MCU Card

WAC RESEARCH CO.,LTD.

Tel : 025303809-10, 025381038

E-mail : sales@wacinfotech.com

www.wacinfotech.com